

HD-TVI CAMERA

FULL HD 1080p Vari-focal IR Bullet Camera

VHC-5230



Technical Specifications

Model No	VHC-5230
Image Sensor	2MP CMOS Image Sensor
Signal System	PAL / NTSC
Effective Pixels	1984(H)*1105(V)
Min. Illumination	0.01 Lux (@ F1.2,AGC ON),0 Lux with IR
Shutter speed	1/25(1/30) s to 1/50,000 s
Lens	2.8 - 12 mm @ F1.4 Angle of view: 105.2° - 32.8°
Lens Mount	φ14
Angle Adjustment	Pan: 0 - 360°, Tilt: 0 - 90°, Rotation: 0 - 360°
Day & Night	ICR
Synchronization	Internal synchronization
Video Frame Rate	1080p@25fps/1080p@30fps
HD Video Output	1 Analog HD output
S / N Ratio	> 62dB
AGC	High / Medium / Low / Off
D/N Mode	Smart IR/Color/BW
White Balance	Auto/Manual
BLC	Support
Language	English
Digital Noise Reduction	Support
Mirror	Support
Working Temperature	-40°C ~ +60°C
Humidity	90% or less (non-condensing)
Power Supply	12 VDC±15%
Power Consumption	Max. 4.5W
Weather Proof Ratings	IP 66
IR Range	Up to 40m
Communication	Up the coax
Dimensions	92 × 84.8 × 269.6mm(3.62" × 3.34" × 10.6")
Weight	690g (1.52 lb)

Key Features

- 2 Megapixel high-performance CMOS
- Analog HD output, up to 2MP resolution
- 2.8-12mm vari-focal lens
- Up to 40m IR distance
- True Day/Night
- OSD menu, 3D DNR, Smart IR
- UTC (Up the Coax) function
- IP66 weatherproof

Dimensions

