

DIGITAL VIDEO RECORDER

32 Channel Turbo HD DVR


VDR-3202P8



Key Features

- Connectable to HDTV1, and Analog cameras
- Up to 32-ch 1080p IP cameras input
- Long distance transmission over coaxial cable
- H.264 compression improves encoding efficiency
- Full channel recording at up to 1080p resolution
- Eight SATA interfaces (up to 4 TB capacity per HDD)
- 32-ch synchronous playback at up to 1080p resolution
- Support P2P and HiDDNS
- Smart search for efficient playback
- Supports Line Crossing and Intrusion Detection
- 2 gigabit Ethernet network interfaces

Rear Panel



Technical Specifications

Model No	VDR-3202P8
Video compression	H.264
HDTV1 and Analog video input	32-ch - BNC interface (1.0 Vp-p, 75 Ω), supporting coaxitron connection
Supported camera types	720p/25Hz, 720p/30Hz, 720p/50Hz, 720p/60Hz 1080p/25Hz, 1080p/30Hz, CVBS
IP video input	16-ch (up to 32-ch) / Up to 2MP resolution
Audio compression	G.711u
Audio input	16-ch / RCA (2.0 Vp-p, 1 KΩ)
HDMI 1 / VGA output	1920 × 1080/60Hz, 1280 × 1024/60Hz, 1280 × 720/60Hz, 1024 × 768/60Hz
HDMI 2 output	1920 × 1080/60Hz, 1280 × 1024/60Hz, 1280 × 720/60Hz, 1024 × 768/60Hz
Encoding resolution	1080p/720p/VGA/WDI/4CIF/CIF
Frame rate	Main-stream: 1080p@12fps; 720p/VGA/WDI/4CIF/CIF@25fps (P)/30fps (N) Sub-stream: WDI/4CIF@12fps; CIF/QCIF/QVGA@25fps (P)/30fps (N)
Video bit rate	32 Kbps to 6 Mbps
Audio output	1-ch, RCA (Linear, 1 KΩ)
Audio bit rate	64 Kbps
Stream type	Video, Video & Audio
Synchronous playback	32-Ch
Remote connection	128
Network Protocols	TCP/IP, PPPoE, DHCP, Hikr Cloud P2P, DNS,DDNS NTP, SADP, SMTP, SNMP,NFS,iSCSI,UPnP,HTTPS
SATA	8 SATA interfaces / Support eSATA
Capacity	Up to 4 TB capacity for each disk
Two-way audio input	1-ch, RCA (2.0 Vp-p, 1 KΩ)
Network interface	2, 10M/100M/1000M self-adaptive Ethernet
Serial interface	RS-232, RS-485, Keyboard
USB interface	3 × USB 2.0
Alarm in/out	16/8
Power Supply	100 to 240 VAC
Consumption	≤ 67 W
Working temperature	-10°C ~ +55°C
Working humidity	10% to 90%
Dimensions	445 × 470 × 90 mm (17.5 × 18.5 × 3.5 inch)
Weight	≤ 8 kg (17.6 lb)