

EXIR HD-TVI CAMERA

5MP EXIR Bullet Camera

VHC-5522



Key Features

- 5 Megapixel high-performance CMOS
- Analog HD output, up to 5MP resolution
- 2.8mm, 3.6mm, 6mm, 8mm, 12mm, 16mm fixed lens
- EXIR technology, up to 80m IR distance
- True Day/Night
- OSD menu, DNR, SMART IR
- UTC (Up the Coax) function
- IP67 weatherproof

Technical Specifications

Model No	VHC-5522
Image Sensor	5MP CMOS Image Sensor
Effective Pixels	2592 (H) × 1944 (V)
Min. Illumination	Color: 0.01 Lux @ (F1.2, AGC ON), 0 Lux with IR
Shutter speed	1/25(1/30)s to 1/50,000s
Lens	2.8 mm,3.6 mm,6 mm,8 mm,12 mm fixed focal lens
Angle of view	86.5° (2.8 mm), 70.1° (3.6 mm), 46° (6 mm), 32.5° (8 mm), 20.9° (12 mm)
Lens Mount	M 12
Angle Adjustment	Pan:0°-360°;Tilt:0°-90°;Rotate:0°-360°
Day & Night	ICR
Synchronization	Internal synchronization
Video Frame Rate	2592 × 1944 @ 20fps
HD Video Output	1 Analog HD output
S / N Ratio	> 62dB
AGC	Support
D/N Mode	Color/BW/SMART
White Balance	ATW/MWB
BLC	Support
Functions	Sharpness,DNR,Mirror,Bad pixel correction,Smart IR
Working Temperature	-40°C ~ +60°C
Humidity	90% or less (non-condensing)
Power Supply	12 VDC±30%
Power Consumption	Max. 5W
Weather Proof Ratings	IP 67
IR Range	Up to 80m
Communication	Up the coax
Dimensions	86.7 mm × 81.6 mm × 226 mm (3.41" × 3.23" × 8.67")
Weight	Approx. 680 g (1.5 lb.)

Dimensions

